

# Adjustable trolley JFB 9 K

High-performance transport trolley from JUNG. The JFB 9 K trolley transports loads up to 9 t with an installation height of 110 mm.

**Product number** 08 091 085-V

**Weight** 31kg



## Product description

Qualities of the transport trolleys JLB 9 K

- Equipped with highest quality castors as standard.
- Reduced weight due to advanced construction of load cassettes.
- All transport trolleys are ready for use: The adjustable-width transport trolley consists of two transport units and connecting bar.
- Inspected according to technical regulation ANSI ? ASME (USA)

The transport trolleys have a low installation height of only 110 mm, allowing them to fit under almost any load. The transport trolleys come with ball bearing supported rollers that enable effortless maneuvering and positioning. These rollers are equipped with a standard wear-resistant coating called "JUWAtan plus", ensuring a smooth and quiet operation. Optionally, the transport trolleys can be equipped with a handle or towing eye for easier transportation.

## Product properties

|   |             |
|---|-------------|
| <b>Castor dimensions (Ø x l mm)</b>         | 85 x 85     |
| <b>Number of castors (Pieces)</b>           | 2 x 6       |
| <b>Height (mm)</b>                          | 110         |
| <b>Supporting surface per cassette (mm)</b> | 170 x 170   |
| <b>Load capacity (t)</b>                    | 9           |
| <b>Load capacity (suitable)</b>             | 16 - 20 t   |
| <b>Connecting bar with joint (mm)</b>       | 1 230       |
| <b>Cassette dimensions (mm)</b>             | 325 x 390   |
| <b>Cassettes adjustable from - to (mm)</b>  | 400 - 1 030 |
| <b>Weight JUWAtan®plus (kg)</b>             | 32          |

More images

