

TIRFOR® and Scafor® hoists for man-riding

TIRFOR®

- For man-riding use

Extra shear pins in handle



model	WLL (kg)	wire rope ø (mm)	guaranteed breaking load	weight (kg)	code
TU-6P	600	8.3	4800	8.4	024639
TU-12P	1200	8.3	9600	11.5	024649
TU-24P	2400	8.3	19.600	16.3	024659

SCAFOR HOIST

- Light weight manual hoist especially designed for light suspended platforms



model	WLL (kg)	wire rope ø (mm)	rope travel for one complete cycle (mm)	effort on each handle for load of 250 kg (kg)	centrifugal break system	breaking strain of rope (kg)	no load safety system	weight (kg)	code
408C	400	8.3	7.5	7	yes	4800	yes	11	016488

MAXIFLEX - ROPES FOR HYDRAULIC TIRFOR®, MAN-RIDING TIRFOR AND SCAFOR MACHINES

- For man-riding, powered and sheaved applications
- All Maxiflex ropes are supplied on a reel terminating with fused and taper at one end and a hook at the other (except 16.3 mm shackle)



diameter end fitting length (m)	Scafor		For use with hydraulic and man-riding Tirfor		
	8.3 mm Scafor c/w hook		11.5 mm c/w/hook		16.3 mm c/w shackle
	code	price	code	price	code
10	490520	88.76	495020	148.32	496520
20	490540	139.33	495050	222.47	496540
30	490600	188.76	495060	297.75	496550
40	490680	237.08	495320	373.04	496570
50	490730	283.15	495070	446.07	496580
60	490760	333.71	495080	520.23	496590
70	490810	383.15	495090	596.63	497080
extra p/m	494500	4.89	493200	7.75	492200