

PALOMAT[®] ½ Pallets

Efficient pallet flow - no manual lifting of pallets

Fully automatic stacking and destacking

You insert or remove the pallets using a hand pallet truck, electric stacker or a full-size forklift truck. All handling is carried out at floor level. The PALOMAT[®] ½ Pallets detects the ½-pallets via photo sensors after which they are fully automatic stacked or destacked one by one.

When selecting destacking, a stack of no more than 15 ½-pallets will be inserted in the PALOMAT[®], after which the pallets are fully automatic destacked one by one. When selecting stacking, the ½-pallets are inserted one by one, after which the pallets are fully automatic stacked to no more

than 15 pallets. The entire stack can subsequently be removed.

PALOMAT[®] ½ Pallets is only operated manually using the touch panel when there is to be a change between stacking and destacking or vice versa. In addition to this, the PALOMAT[®] ½ Pallets operates fully automatic.

The PALOMAT[®] can handle all 4-way pallets in wood, plastic and metal no matter what the length, width or height.

We can customise the PALOMAT[®] to exactly match the pallet size you use.



Your benefits with PALOMAT[®]

- Space saving and a tidy workplace
- Optimised pallet flow
- Improved work environment
- Reduced pallet costs
- Increased efficiency
- No manual pallet handling
- Less absence due to illness
- Reduced time spent per pallet
- Fewer back injuries, jammed fingers and feet
- Less truck driving
- Leaner – increased efficiency with less resources
- "Plug and Play" solution



Models				
Article no.	Machine dimensions L x W x H (mm)	Pallet size L x W x H (mm)	Lifting capacity	No. of pallets
152050	935x1450x2350*	600x800x150	500 kg	15 pallets
150050	935x1450x2350*	600x800x150	500 kg	15 pallets

Technic
Power source
220-240V AC, 50 Hz
6-7 bar + 100-240V AC, 50 - 60Hz

Option
Pallet handling in cold environments
Down to - 25 C° / - 13 F°

* Incl. safety frame for 15 pallets with gate which is required

Control: Siemens S7-1200
Actuator: Linak
Pneumatics: SMC

Standard colours: RAL 3002 red, RAL 5002 blue, RAL 7032 grey and RAL 7035 grey

You can read more about PALOMAT[®] ½ Pallets, options, technical data etc. on www.palomat.com

